Application

Medium hard, one-sided PET carrier foam tape with 500 micron (20 mil) application thickness and differential acrylic adhesives on each side. Especially for mounting of stiff or thick photopolymer plates (≥ 2.54 mm (0.1")) on composite and urethane sleeves or print cylinders with small to normal diameter in the flexible packaging an pre-print industry (wide web process).

Construction

Thickness without liner*	approx. 550 micron (22 mil)
Liner	embossed PP film, 110 micron, white
Adhesive, closed side	acrylic, high adhesion
Carrier	medium hard PE foam, grey (Orafol Logo) on plate side
Adhesive, open side	acrylic, enhanced adhesion


^{*} average

Product Properties

- Medium hard plate mounting tape
- 500 micron (20 mil) application thickness
 - Hardness grade "medium" indicated by the grey colour code
 - Minimum thickness tolerances
 - Differential acrylate with high adhesion to plate and cylinder / sleeve for a secure mounting without edge-lifting
 - Easy and clean demounting
 - Easy repositioning
 - Embossed liner enables plate mounting without air entrapments

Application fields

- especially suitable for fine lines, halftones and process printing
- · combination of solid and screen



JRAFLEX® 11826 soft



ORAFLEX® 11856 medium



ORAFLEX® 11886 firm

IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.

