

Description

This one-sided adhesive tape consists of a water soluble modified acrylate adhesive, coated on a repulpable one sided siliconised paper. It has a strong tack and excellent thermal resistance.

Carrier

Water repulpable paper, silicone coated on one side, white, 70 g/m²

Liner

Without liner

Adhesive

Modified acrylate, water soluble, colourless

Area of use

Water repulpable splicing tape with normal thickness and high thermal resistance for universal applications, manual splice roll changes and for fixing of the end of the rolls.

The used adhesive RA4 meets the demands of the Code of Federal Regulations, Food and Drugs (FDA), 21 CFR Ch. I (April 1, 2008 edition), § 175.105.

Technical Data

Thickness* (adhesive + carrier)	100 micron
Temperature resistance***	up to +200° C, momentary up to +230° C
Loop Tack* (FINAT TM 9)	12 N/25 mm
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 7 N/25 mm after 20 min: 8 N/25 mm
Shear strength* (S.A.F.T. Test from 23° C up to 230° C)	90 min/+220° C
Tensile strength* (DIN EN ISO 527)	along: 160 N/25 mm across: 80 N/25 mm
Repulpability (according to TAPPI UM 213)	meets requirements
Shelf life**	12 months in closed original packing
* average ** in original packaging, at 20° C and 50% re	

IMPORTANT NOTICE

All ORAFIX[®] products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFIX[®] products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFIX[®] products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFIX[®] is a registered trademark of ORAFOL Europe GmbH.

